



# PROSEAL PLUS



GLOBCON PROSEAL PLUS is a reactive microemulsion based solventless waterproofing and water-repelling agent that seals the micropores of the substrate. It has the super ability to penetrate inside the substrate and becomes a permanent integral part of the structure. It makes the surface hydrophobic preventing water absorption. Globcon Proseal Plus can be diluted with water, It can be applied with brush, spray and other methods. Globcon Proseal Plus is UV Resistant, Breathable and doesn't change the look of the surface. It is specially formulated for those surfaces where darkening is unacceptable.

## RECOMMENDED APPLICATION

- Internal & External surfaces
- Expose concrete
- Expose brickwork
- Expose blockwork
- Mineral plasters
- Porous stone Precast concrete
- Drywalls & cement sheets
- Interior/ Exterior walls
- Wet areas
- Roofs
- Terraces
- Gardens

## BENEFITS & KEY FEATURES



**EASY TO APPLY**



**ECONOMICAL**



**BREATHABLE**



**HIGH WATER REPELLECE**



**WEATHER PROOF**



**PROTECT FROM FUNGUS AND ALGAE**

## DIRECTION FOR USE

### SURFACE PREPARATION



Prepare the surface thoroughly by cleaning, washing dust, dirt, oil, grease and loose particles. All new renderings, masonry /concrete surfaces should be allowed to age 6 to 8 weeks before surface coating. All surface cracks up to 5 mm width should be filled up using proper crack filling material like crack filler or acrylic sealant. Any areas which need to be repaired should be treated with proper procedure.

## APPLICATION

### MIXING & APPLICATION



- PROSEAL PLUS can be diluted with water in a ratio of 1:15 upto 1:20 (PROSEAL PLUS:Water). mix the desired quantity in a vessel for 10-15 min.
- The product can be applied by brush, roller, flooding, or spray method.
- PROSEAL PLUS must be applied until the substrate is saturated.
- At least two wets on wet coats are needed for complete coverage.
- A low-pressure sprayer can also be used for application.
- Extra coat may be needed as per requirement.
- Let it dry for 24 hours.

## NOTE

Always apply a test patch in an inconspicuous area and confirm the results are acceptable for continuing. Application should not be done under peak sun hours or extreme heat conditions.

## TECHNICAL SPECIFICATION

Appearance	Slightly Yellowish Clear Liquid
Solid Content	100%
Specific Gravity	0.95 - 0.97 g/cm <sup>3</sup>
Mix Ratio	1: 15-20 (PROSEAL PLUS : WATER)
Drying Time	24 Hours

PACKAGING	COVERAGE	SHELF LIFE
500 ml, 1 Ltr & 5 Ltr containers	600 Sq.Ft / 21 Ltr solution (1 PROSEAL PLUS: 20 water) Factors like surface porosity mix. ratio, temperature and application method can alter consumption.	24 months from date of packing. It must be seal pack & stored under proper condition. Store in a cool & dry place, keep away from direct sunlight.

