



TERRARUFF



TERRARUFF is a two-component innovative solution composed of Hydraulic binders, Polymers, Graded fillers and emulsions to develop a mechanical key or rough surface over substrates. It helps to create rough texture over all types of Ceramic tile, Vitrified Tile, Walls, Natural Stones & Agglomerates. It has superior bond strength and compatibility over a variety of substrate. It is manufactured by employing state-of-the-art emulsion polymerization technology, ensuring product consistency. These features make it a premium choice for installing tile & stone in high demanding areas such as external facades, industrial floor and high traffic areas etc.

RECOMMENDED APPLICATION SUBSTRATE

- Ceramic
- Granites
- Precast
- Vitrified Tiles
- Stones
- Concrete
- Cement Surfaces
- Artificial Stones
- Marbles
- Mivan
- Fibre Board
- Quartz Stones
- Composites Stones

BENEFITS & KEY FEATURES



Extra Grip



Better Surface



Durability



Easy Application



Compatibility



High Bond Strength

TECHNICAL SPECIFICATION

Appearance	Part (A) Milky White Liquid Part (B) Grey Powder
Pot Life	30 Minutes @ 25oC
Tensile Split Strength	> 1 n/mm ²
Shear Strength	> 2 Mpa
Recommended Thickness	2 mm
Mixing Ratio	2:1 (Powder:Liquid)

*Consult with our technical advisor for cladding Applications for interior/exterior and horizontal/vertical applications. • Specifications may vary due to continuous product development.

PACKAGING	COVERAGE	SHELF LIFE
3 Kg (Part A=1 Ltr, Part B=2 kg)	16 sq. ft/ per kg mix.	12 months from the date of packing.
15 Kg (Part A=5 Ltr, Part B=10 kg)	coverage is depends on the surface	Should be stored in cool & dry condition, keep away from direct sunlight.
60 Kg (Part A=20 Ltr, Part B=40 kg)	conditions part mixing of materials is strictly prohibited	
Part A = Liquid Part B = Powder		

DIRECTION FOR USE

SURFACE PREPARATION



Prepare the surface thoroughly by cleaning, washing, removing dust, dirt, oil, grease and loose particles. The surface must be sound. Cementitious surfaces which are unstable should be treated with necessary repair or patchwork system using GLOBCON LEAKPROOF 360 or GLOBCON ULTRA SBR.

MIXING



- Stir or shake liquid component before use.
- Add 2 parts of (B) and 1 part (A) of liquid in a vessel.
- Mix it properly with proper tools or stirrer.
- Brush apply the material on the surface.
- Allow it to dry.
- Maintain the desired thickness of the material.
- Application on tiles or stones should be done by making patch grids at regular internals.

NOTE

- Do Not Dilute With Water
- Drying Time Depends Upon The Weather Conditions.

HEALTH AND SAFETY

- Wear suitable protective clothing, gloves, eye protection and respiratory protective equipment during application
- In case of contact with skin, rinse with plenty of clean water and then cleanse with soap water
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.

